

Consep-CT

Oil/Water separators



PRODUCT FEATURES

The Consep-CT range of oil/water separators separates oil from condensate, generated by compressed air systems.

The Consep-CT achieves efficient separation of oil from condensate by means of directing the condensate through various separation stages. As condensate flows in to the Consep-CT, the oil is filtered out through various filtration elements.

The Consep-CT uses adsorption filter materials, instead of a weir, to remove the bulk of the oil.

The life of the Consep-CT first stage filtration element is determined by the amount of oil removed, not by the amount of condensate treated.

The Consep-CT carbon element is utilised only for final purification purposes and ensures that the targeted values of <10 ppm are achieved.

The professional design of the Consep-CT is incredibly compact and the elements are lightweight, maximising the ergonomic factors when carrying out routine maintenance.

Brass connection inserts ensure a secure fixing of the condensate inlets and outlet connections.



COMMERCIAL BENEFITS

- Operates with all type condensate drains (both timer controlled and level sensed)
- Three models covering up to 15 m³/m in compressor capacity offering sizing flexibility
- Freight cost advantages, even the largest model can be sent as a parcel shipment

TECHNICAL ADVANTAGES

- Small foot print
- Light and easy replacement of elements
- Simple installation and maintenance procedures
- Sample bottle and test drain for output testing/measuring the ppm value (indication)
- Overflow safety indicator.
- All type drains can be used in combination with the Consep-CT

Consep-CT

Oil/Water separators



TECHNICAL SPECIFICATIONS

Model	CT 3 (3 m ³ /min.)	CT 7 (7 m ³ /min.)	CT 15 (15 m ³ /min.)
Target oil output value	<10 ppm	<10 ppm	<10 ppm
Max. oil adsorption (litres)	3	7	15
Inlet connections (brass)	1/2" (1)	1/2" (1)	1/2" (2)
outlet connections (brass)	1/2"	1/2"	1/2"
TEST valve (brass)	Yes	Yes	Yes
Overflow indicator	Yes	Yes	Yes
Housing material	PPC	PPC	PPC
Total recyclable	Yes	Yes	Yes
Housing colour	Grey	Grey	Grey
Standard lid colour	Blue	Blue	Blue

SEPARATION OF:

Mineral lubricants	Yes
Synthetic lubricants	Yes
Stabile condensate emulsions*	Yes
Polyglycol*	Yes

**Special elements required, please consult us*

ADDITIONAL FEATURES

All Consep-CT models can accept condensate discharge from efficient intelligent drains, cost effective timer drains, float drains and manual drains.

Consult us for:

- * Larger compressor capacities
- * Special element solutions
- * Element selection condensate test kit

Hi-Line Industries

Green Street
Burton-Upon-Trent
Staffordshire
DE14 3RT

Tel: 01283 533 377
Fax: 01283 533 367

E-Mail: enquiries@hilineindustries.com